

9330N/9330ND



Transform Your Business

Small and Efficient

Ideally suitable for workgroups or small networks, the feature rich 9330 range of mono laser printer will transform your documents increasing overall efficiency in your office.

True 1200 dpi print quality coupled with a very respectable 28 page per minute A4 will ensure the 9330 range, delivers professional quality output all within your budget.

Choice of Models

The 9330N offers two input paths, a 250 sheet cassette together with a 50 sheet multi-purpose feeder ideal for those non standard paper sizes . PCL and PostScript 3 is standard together with 64 Mb of onboard memory expandable to 320 Mb, will ensure the 9330N will speed through the most complex applications.

For Duplex printing the 9330ND comes complete with its own inbuilt duplex feeder for fuss free double sided printing on a wide variety of paper types and sizes. Both models can benefit from an additional optional 250 sheet cassette which can be simply installed by the user.

Versatile

USB 2 is standard on all models for high use personal users together with Ethernet 10/100BaseT and parallel, making the 9330 the most versatile range printers available today. PCL and postscript together with a range of Windows driver setup utilities will ensure the 9330 will connect to virtually anything.

Mono Laser

Colour Laser

Mobile

Serial Matrix

Line Matrix

Consumables

- 1200 x 1200 dpi print quality
- 8.5 Seconds first time to print
- Ideal for workgroups or small networks
- Up to 30 ppm letter 28 ppm A4
- Choice of models Simplex or Duplex
- Small and compact design
-

9330N/9330ND

Features & Specifications

Mono Laser Printer

Printer Type	9330N/9330ND
Printing Technology	Laser
Processor	SPGPM, 400MHz
Print Speed	Simplex (9330N) , Up to 30 pages per minute letter, 28 pages per minute A4, Duplex (9330ND) Up to 21 pages per minute letter, Up to 19 pages per minute A4
Monthly Workload	Up to 35,000 pages per month max, 4,000-7,000 per month average
Print Resolution	1200 x 1200dpi
Memory - Standard	64Mb
Memory - Maximum	320Mb
Emulation - Standard	PCL6/PCL5e/IBM Proprinter / Epson Postscript Level 3 PDL/Barcode
Emulation Intelligence	Automatic Emulation Sensing
Fonts	1 Bit Map and 45 scalable (35 Intellifont, 10 TrueType), 136 PS3 fonts
Paper handling input - Standard	Manual feed, 50 sheet multi-purpose feeder (MPF) plus 250 sheet universal cassette
Paper handling input - Optional	2nd universal cassette accepts 250 sheets
Paper handling output - Standard	150 sheet face down 1 sheet face up
Duplex	Automatic on 9330ND Manual on 9330N (driver support provided)
Print media type	MPF - paper, transparencies, labels, heavy paper stock, envelopes Standard cassette - paper Optional cassette - paper
Paper sizes	MPF - A4, A5, A6, Letter, Legal, Folio, Executive, ISO B5, JIS B5, 3" x 5". Standard Cassette - A4, A5, Letter Legal, Folio, Executive ISO B5, JIS, 3" x 5" Optional Cassette - A4, A5, Letter, Legal, Folio, Executive ISO B5, JIS, 3" x 5" Duplex - A4, Letter, Legal, Oficio, Folio
Envelope sizes	Monarch, No 9, No 10, C5, DL
Non-printable area	Paper - 4mm from each side, 10 mm from top and bottom
Media weight	Cassette - 60-90gsm MPF - 60-163 gsm Duplex 75-90 gsm
Interfaces - Standard	Parallel (Bi-directional IEEE 1284 compliant ECP/Nibble/Byte Mode), USB (v 2.0), Internal Ethernet (10BaseT & 100BaseTx),
Interface Intelligence	Automatic Interface Switching
Printer Drivers	Windows 9.x/NT 4.0/2000/XP/ME/MAC Posters, N-Up, Booklets, Duplex, Forms, Overlays, Watermarks
Network Utilities	SyncThru, SET IP
DOS Print	Available
First page print	Less than 8.5 seconds
Warm up time	Less than 43.5 seconds
Environmental ozone	Less than 0.02 parts per million (UL478)
Acoustic level (ISO 7779)	Printing - 54 dBA, Standby - 39 dBA, Sleepmode - Background Level
Weight	<10.6kg including consumable
Dimensions	400(w) x 433(d) x 285(h) mm
Input Voltage	220-240V 50/60Hz
Power Consumption	Energy Star Compliant, Less than 11 watts in sleep mode, Less than 900 watts printing (average)
Operating Environment - Temperature	10°C - 32°C
Operating Environment - Humidity	10% - 80% relative humidity, non-condensing
Operating Altitude	2,500 metres (maximum)
MPBF	30,000 pages (Power on 8 hr/day in recommended duty cycle)
MTTR	30 minutes
Consumables	High Yield: Replacement process unit - 8,000 pages Normal Yield: Replacement process unit - 4,000 pages Starter Process Unit Cartridge 4,000 per page Based on 5% coverage of A4 page (ISO mSO/IEC 19752 TBA)
Options	2nd cassette (250 sheet), 16/32/64/128Mb.
Warranty	2 years (Hotswap). Installation free of charge, mainland UK & Eire



Rutherford Road, Basingstoke,
Hampshire, RG24 8PD.

Tel: UK 0800 652 4557

International: +44 (0) 1256 481 521

Fax: UK 0870 872 2889

Web: www.tallygenicom.co.uk